



GELATO PRO 5K

made
in
ITALY



PROFESSIONAL CLASS



NEMOX S.p.A.
Via Enrico Mattei, n.14
I-25026, Pontevedico (Brescia) ITALY

CHIAMA IL NUMERO
848 800 515
A SERVIZIO CLIENTI
di tutto il territorio urbano





DATI TECNICI	TECHNICAL SPECIFICATIONS	TECHNISCHE EIGENSCHAFTEN	DONNEES TECHNIQUES	CARACTERÍSTICAS TÉCNICAS	
Alimentazione	Rating	Stromversorgung	Alimentation	Alimentación	220-240V 50Hz 220V 60Hz 120V 60 Hz 500 W - 1 Phase
Raffreddamento ad aria	Air cooling	Luftkühlung	Refroidissement par air	Enfriamiento por aire	•
Capacità vasca mantecazione	Bowl capacity	Fassungsvermögen	Capacité cuve de mélange	Capacidad tanque de mantecacion	3,2l.
Quantità max ingredienti	Max ingredients qty	Max. Zutatenmenge	Quantité max. ingrédients	Cantidad max.ingredientes	1,5 Kg
Tempo di preparazione	Preparation time	Zubereitungszeit	Temps de préparation	Tiempo de preparación	15'
Produzione max oraria	Max production/hour	Max. Herstellung /Std	Production max.horaire	Producción max. horaria	5Kg.
Coperchio di chiusura in policarbonato	Unit cover in PC	Deckel aus PC	Couvercle en PC	Tapadera PC	•
Sicurezze elettriche blocco pala ad apertura coperchio	Electrical safety -paddle block on opening of the cover	Stromschutvorrichtung - Rührwerkstopp bei Deckelöffnung	Sécurités électriques bloc pale lors de l'ouverture du couvercle	Seguridad eléctrica bloqueo de la pala al abrir la tapadera	•
Compressore Ermetico	Hermetic Compressor	Kompressor	Compresseur hermétique	Compresor hermético	100% CFC Free 14 cc
Gas impiegato	Gas used	Verwendetes Gas	Gaz employé	Gas empleado	R404a
Potenza compressore	Compressor power	Kompressor Leistung	Puissance compresseur	Potencia compresor	330W
Motore mescolamento ad induzione con termostato	Mixing motor -induction with thermostat	Rührwerkmotor -Induktion mit Thermostat	Moteur mélange à induction avec thermostat	Motor de mezcla a inducción con termostato	•
Sicurezze termiche compressore e mescolatore	Thermic safety for compressor and mixing motor	Thermoschutzvorrichtung - Kompressor und Rührwerk	Sécurités thermiques compresseur et mélangeur	Seguridad térmica -compresor y mezclador	•
Riduzione a ingranaggi	Reduction gear box	Untersetzungsgetriebe	Reduction à engrenages	Reducción à engrénaje	63 rpm
Timer	Timer	Timer	Temporisateur	Temporizador	30min
Cestello estraibile	Includes one stainless steel removable bowl	Mit entfernbarem Behälter aus rostfreiem Edelstahl	Livré avec cuve amovible en acier inox	Recipiente extraíble de acero inox - incluido	inox
Pala di mescolamento in acciaio con inserti in tecnopolimero	Mixing paddle in steel with inserts in tecnopolimer	Edelstahl Ruhrspatel mit Technopolymer-Einlage	Pale mélangeuse en acier avec insertions en technopolymère	Paleta mezcladora en acero con insertos en tecnopolimero	•
Carrozzeria in acciaio inox	Stainelss steel body	Gehäuse aus rosfreiem Edelstahl	Carrosserie en acier inox	Carrocería en acero inox	•
Larghezza	Width	Breite	Largeur	Ancho	mm 450 - inch 17,72
Profondità	Depth	Tiefe	Profondeur	Profundidad	mm 490 - inch 19.30
Altezza	Height	Höhe	Hauteur	Altura	mm 370 - inch 14,57
Peso netto	Net Weight	Netto Gewicht	Poids Net	Peso Neto	33 Kg - 72,75 lbs